



FIRING CONFIGURATIONS

Windham Weaponry models are available in these configurations:

Safe / Semi-Auto / Full-Auto

Full-Auto Rate of Fire is a minimum of 700 rounds per minute.

Safe/Semi/Full-Auto Receiver Markings

For pricing, contact Windham Weaponry's International Sales Manager at export@windhamweaponry.com

RM16M4A4T-762 MODEL SPECIFICATIONS:

Caliber: 7.62x39	Barrel Material: 4150 Chrome Moly Vanadium 11595E Steel with M4 Feed Ramps
Action: Gas Impingement System — Safe / Semi Auto / Full Auto	Rifling: 1 in 9.5" - Right Hand Twist
Capacity: 30 + 1 - Ships with one 30 Round Magazine (accepts all std. sizes)	Stock: 6-Position Telescoping Buttstock
Safety: Manual Lever with Indicator Markings on Both Sides of Receiver	Forend: M4 Fiberglass Double Heat Shield Hand Guard
Receiver: A4 Flat Top Type Upper Receiver w. A4 Removable Carry Handle	Pistol Grip: A2 Black Plastic Grip
Receiver Material: Forged 7075 T6 Aircraft Aluminum with Aluminum Trigger Guard	Rear Sight: A4 Dual Aperture Elevation & Windage Adjustable: 300 - 600 M
Receiver Finish: Hardcoat Black Anodize Finish	Front Sight: A frame Fixed Front Sight Post
Bolt Material: Carpenter 158 Steel	Weight: 6.74 lbs. without magazine (3.06 kg)
Barrel: 16" M4 Profile, Chrome Lined with A2 Flash Suppressor	Length: 35.5" / 31.5" with Telestock collapsed

Includes: Hard Plastic Case / Sling / Chamber Safety Plug / 30 Rd. Magazine